

Machine Name

## Flexiheat Unit



Description

ATEX certified Heater with airflow of 3110m<sup>3</sup>/hour. 2 units can be connected for even more efficiency.

Nominal output: 15Kw @ 400VAC

Supplied with antistatic ducting hose for channelling the air to vessels etc.

### Technical data

Size (L x W x H):	690 x 560 x 580 mm
ATEX Classification:	Zone 1 - Ex II 2G c IIB T3
Unit Weight:	53 kg
Power Supply:	400 VAC

Current:	23 Amp - start up 24 Amp.
Airflow:	3110 m <sup>3</sup> /h
Achieved Temperature:	15°C Temperature rise

### Equipment view



### Related products



**Heatbox Paint Heater ATEX** is a compressed air driven heater unit. The unit is produced in a compact design and can be used in Zone 1 areas. Heats two 20 litre paint buckets.



**Ex Fan Heater Zone 2** used for comfort heating and heating of storage facilities such as tents, containers etc. Often used by painters. A very silent mobile heating solution with built-in...



**Paint Pre-Heater** - is a machine for efficient and fast heating of paint material. Frame design with fork lift pockets and chain sling for easy manoeuvrability, fill it with water, plug in...

For more details please contact:

**Claus Engelbrecht Jensen**

Telephone: +45 4697 5212

E-mail: [cej@pm.dk](mailto:cej@pm.dk)