

Maskine navn

Flexiheat Unit



Beskrivelse

ATEX certificeret Heater med luftflow på 3110m³/hour. 2 enheder kan sammenkobles for øget effektivitet.

Nominal output: 15Kw @ 400VAC

Leveres med antistatisk ventilationslange for transport af luft til tanke, rum etc.

Tekniske data

Størrelse (L x B x H):	690 x 560 x 580 mm
ATEX Klassifikation:	Zone 1 - Ex II 2G c IIB T3
Vægt:	53 kg
Strømforsyning:	400 VAC

Strøm:	23 Amp - start up 24 Amp.
Luftflow:	3110 m ³ /h
Opnået temperatur:	15°C Temperature rise

Udstyr visning



Relaterede produkter




Heatbox Paint Heater ATEX

Heatbox Paint Heater ATEX is a compressed air driven heater unit. The unit is produced in a compact design and can be used in Zone 1 areas. Heats two 20 litre paint buckets....



Ex Fan Heater 9300

Ex Fan Heater Zone 2 used for comfort heating and heating of storage facilities such as tents, containers etc. Often used by painters. A very silent mobile heating solution with built-in thermostat....



Paint Pre-Heater

Paint Pre-Heater - is a machine for efficient and fast heating of paint material. Frame design with fork lift pockets and chain sling for easy manoeuvrability, fill it with water, plug in electrical supply for heating etc...

For yderligere information kontakt venligst:

Claus Engelbrecht Jensen

Telefon: +45 4697 5212

E-mail: cej@pm.dk